

Project 4 Inter-Process Communication and Process Management

COS 318

Fall 2015

Project 4: IPC and Process Management



- Goal: Add new IPC mechanism and process management to the kernel.
- Read the project spec for the details.
- Get a fresh copy of the start code from the lab machines. (/u/318/code/project4/)
- Start as early as you can and get as much done as possible by the design review.

Project 4: Schedule



- Design Review:
 - Thursday 11/19
 - Sign up on the project page;
 - Please, draw pictures and write your idea down (1 piece of paper).
- Due date: Tuesday, 11/24, 11:55pm.

Project 4: Overview



- Implement a spawn system call.
- Implement inter-process communication using message boxes.
- Implement a handler for the keyboard interrupt.
- Implement a kill system call.
- Implement a wait system call.

Design Review



- Design Review:
 - Answer the questions:
 - ✓ Process Management:
 - ♦ How will your spawn, wait, and kill work?
 - How will you satisfy the requirement that "if a process is killed while blocked on a lock, semaphore, condition variable or barrier, the other processes which interact with that synchronization primitive [will] be unaffected?

✓ Mailboxes:

- ♦ What fields will the structs need?
- ♦ Which synchronization primitives will you use?

Implementation Checklist



- do spawn: creates a new process
- do_mbox_*: mbox functions to enable IPC
 - open, close, send, recv, is_full.
- Handle keyboard input:
 - putchar();
 - do getchar();
- do kill(): kills a process.
- do wait(): waits on a process.

Spawn



- Kernel has a fixed array of PCBs.
- What info do you need to initialize a process?
 - PID
 - New stacks (user/stack)
 - Entry point (ramdisk_find)
 - total_ready_priority (lottery scheduling)
- Scheduler uses lottery scheduling: make sure you keep the sum of the priorities updated.

Message Boxes



- Bounded buffer:
 - Has fixed size;
 - FIFO;
 - Variable size message.
- Multiple producers:
 - Put data into the buffer.
- Multiple consumers:
 - Remove data from the buffer.
- Blocking operations:
 - Sender blocks if not enough space;
 - Receiver blocks if no message.
- Review Lecture 11 on Message Passing.
- Read MOS 2.3.7 and 2.3.8.

Mailbox – Implementation



- Buffer management:
 - Circular buffer: head and tail pointers.
- Bounded buffer problem:
 - Use locks and condition variables to solve this problem as shown in class;
 - Two condition variables: moreData and moreSpace (or any other names you prefer).

Keyboard – Overview



- How does the keyboard interact with the OS?
 - A hardware interrupt (IRQ1) is generated when a key is pressed or released;
 - Interrupt handler talks to the hardware and gets the scan code of the pressed/released key;
 - If it is SHIFT/CTRL/ALT/..., some internal states are changed;
 - Otherwise the handler converts the scan code into an ASCII character depending on the states of SHIFT/ NUM LOCK/...

Keyboard – Overview



- How does the keyboard interact with the OS?
 - init_idt() in kernel.c sets handler to irq1_entry in entry.S;
 - irq1_entry calls keyboard_interrupt in keyboard.c;
 - keyboard_interrupt talks to the hardware and gets the scan code back (key = inb(0x60)) and calls the key specific handler;

Keyboard – Overview



- If key is SHIFT/CTRL/ALT/..., some internal states are changed.
- Otherwise normal_handler converts the scan code into an ASCII character.
- normal_handler calls putchar() to add character to the keyboard buffer.
- You need to implement putchar().
- You also need to implement do_getchar(), which is called by the shell via syscall (get_char).

Keyboard – Implementation



- It is a bounded buffer problem:
 - Use mailbox.
- But, there are some variations:
 - Single producer (IRQ1 handler);
 - Multiple consumers (more than one process could use keyboard);
 - Producer cannot block discard character if buffer is full.

Keyboard – Implementation



- Producer should not be blocked:
 - Solution: check and send message only if mailbox is not full, otherwise discard it.
 - Use the function do_mbox_full().
- Is that all?
 - What if a process being interrupted by IRQ1 is currently calling get_char()?
 - Address how to fix this issue in the design review.

Kill



- A process should be killed immediately.
 - Which queue it is in (ready, blocked, sleeping, etc.)
 doesn't matter kill it!
- Do not reclaim locks (this is extra credit).
- Reclaim memory:
 - PCB;
 - Stacks;
 - Look at robinhood test case to figure out what else needs to be reclaimed.
- Update total_ready_priority.

Wait



- Waits for a process to terminate:
 - Blocks until the process is killed or exits normally.
- What do you need to add to the PCB to implement this behavior?
- Return -1 on failure, 0 on success.

Hints/Tips



- List of functions to implement is straightforward.
 But, realizing the implementation is tricky!
- Look at util.h and check out any of the header files in the project folder for a helper function you might want.
- Use the settest script (two tests provided).
- You will need to change data structures and functions that are not annotated with TODO in the source code.