

fraction2.js (Page 1 of 2)

```

1: //-----
2: // fraction2.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const euclid = require('./euclid.js');
9:
10: function createFraction(num=0, den=1)
11: {
12:     if (arguments.length > 2)
13:         throw new Error('Too many arguments');
14:
15:     if (den === 0)
16:         throw new Error('Denominator cannot be zero');
17:
18:     let f = {};
19:
20:     f._num = num;
21:     f._den = den;
22:
23:     if (f._den < 0) {
24:         f._num *= -1;
25:         f._den *= -1;
26:     }
27:     if (f._num === 0)
28:         f._den = 1;
29:     else {
30:         let gcden = euclid.gcd(f._num, f._den);
31:         f._num /= gcden;
32:         f._den /= gcden;
33:     }
34:
35:     f.toString = function() {
36:         return String(this._num) + '/' + String(this._den);
37:     };
38:
39:     f.compareTo = function(other) {
40:         if ((this._num * other._den) < (other._num * this._den))
41:             return -1;
42:         if ((this._num * other._den) > (other._num * this._den))
43:             return 1;
44:         return 0;
45:     };
46:
47:     f.negate = function() {
48:         return createFraction(-this._num, this._den);
49:     };
50:
51:     f.add = function(other) {
52:         let newNum = (this._num * other._den) + (other._num * this._den);
53:         let newDen = this._den * other._den;
54:         return createFraction(newNum, newDen);
55:     };
56:
57:     f.subtract = function(other) {
58:         let newNum = (this._num * other._den) - (other._num * this._den);
59:         let newDen = this._den * other._den;
60:         return createFraction(newNum, newDen);
61:     };
62:
63:     f.multiply = function(other) {
64:         let newNum = this._num * other._num;
65:         let newDen = this._den * other._den;

```

fraction2.js (Page 2 of 2)

```

66:         return createFraction(newNum, newDen);
67:     };
68:
69:     f.divide = function(other) {
70:         let newNum = this._num * other._den;
71:         let newDen = this._den * other._num;
72:         return createFraction(newNum, newDen);
73:     };
74:
75:     return f;
76: }
77:
78: module.exports = { createFraction };

```

fraction2client.js (Page 1 of 2)

```

1: //-----
2: // fraction2client.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const readlineSync = require('readline-sync');
9: const fraction = require('./fraction2.js');
10:
11: //-----
12:
13: function readInt(prompt) {
14:   let line = readlineSync.question(prompt);
15:   if (line === '') {
16:     throw new Error('Missing integer');
17:   if (isNaN(line)) {
18:     throw new Error('Not a number');
19:   let n = Number(line);
20:   if (!Number.isInteger(n))
21:     throw new Error('Not an integer');
22:   return n;
23: }
24:
25: //-----
26:
27: function main() {
28:   try {
29:     let n1 = readInt('Numerator 1: ');
30:     let d1 = readInt('Denominator 1: ');
31:     let n2 = readInt('Numerator 2: ');
32:     let d2 = readInt('Denominator 2: ');
33:
34:     let f1 = fraction.createFraction(n1, d1);
35:     let f2 = fraction.createFraction(n2, d2);
36:
37:     process.stdout.write('f1: ' + f1.toString() + '\n');
38:     process.stdout.write('f2: ' + String(f2) + '\n');
39:
40:     if (f1 === f2)
41:       process.stdout.write('f1 is identical to f2\n');
42:     else
43:       process.stdout.write('f1 is not identical to f2\n');
44:
45:     let compare = f1.compareTo(f2);
46:     if (compare < 0)
47:       process.stdout.write('f1 is less than f2\n');
48:     if (compare > 0)
49:       process.stdout.write('f1 is greater than f2\n');
50:     if (compare === 0)
51:       process.stdout.write('f1 is equal to f2\n');
52:
53:     let f3;
54:
55:     f3 = f1.negate();
56:     process.stdout.write('-f1: ' + String(f3) + '\n');
57:
58:     f3 = f1.add(f2);
59:     process.stdout.write('f1 + f2: ' + String(f3) + '\n');
60:
61:     f3 = f1.subtract(f2);
62:     process.stdout.write('f1 - f2: ' + String(f3) + '\n');
63:
64:     f3 = f1.multiply(f2);
65:     process.stdout.write('f1 * f2: ' + String(f3) + '\n');

```

fraction2client.js (Page 2 of 2)

```

66:
67:     f3 = f1.divide(f2);
68:     process.stdout.write('f1 / f2: ' + String(f3) + '\n');
69:   }
70:   catch (e) {
71:     process.stderr.write(String(e) + '\n');
72:   }
73: }
74:
75: if (require.main === module)
76:   main();

```

fraction3.js (Page 1 of 2)

```

1: //-----
2: // fraction3.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const euclid = require('./euclid.js');
9:
10: function Fraction(num=0, den=1) {
11:     if (arguments.length > 2)
12:         throw new Error('Too many arguments');
13:
14:     if (den === 0)
15:         throw new Error('Denominator cannot be zero');
16:
17:     this._num = num;
18:     this._den = den;
19:
20:     if (this._den < 0) {
21:         this._num *= -1;
22:         this._den *= -1;
23:     }
24:     if (this._num === 0)
25:         this._den = 1;
26:     else {
27:         let gcden = euclid.gcd(this._num, this._den);
28:         this._num /= gcden;
29:         this._den /= gcden;
30:     }
31:
32:     this.toString = function() {
33:         return String(this._num) + '/' + String(this._den);
34:     };
35:
36:     this.compareTo = function(other) {
37:         if ((this._num * other._den) < (other._num * this._den))
38:             return -1;
39:         if ((this._num * other._den) > (other._num * this._den))
40:             return 1;
41:         return 0;
42:     };
43:
44:     this.negate = function() {
45:         return new Fraction(-this._num, this._den);
46:     };
47:
48:     this.add = function(other) {
49:         let newNum = (this._num * other._den) + (other._num * this._den);
50:         let newDen = this._den * other._den;
51:         return new Fraction(newNum, newDen);
52:     };
53:
54:     this.subtract = function(other) {
55:         let newNum = (this._num * other._den) - (other._num * this._den);
56:         let newDen = this._den * other._den;
57:         return new Fraction(newNum, newDen);
58:     };
59:
60:     this.multiply = function(other) {
61:         let newNum = this._num * other._num;
62:         let newDen = this._den * other._den;
63:         return new Fraction(newNum, newDen);
64:     };
65:
```

fraction3.js (Page 2 of 2)

```

66:     this.divide = function(other) {
67:         let newNum = this._num * other._den;
68:         let newDen = this._den * other._num;
69:         return new Fraction(newNum, newDen);
70:     };
71: }
72:
73: module.exports = { Fraction };

```

fraction3client.js (Page 1 of 2)

```

1: //-----
2: // fraction3client.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const readlineSync = require('readline-sync');
9: const fraction = require('./fraction3.js');
10:
11: //-----
12:
13: function readInt(prompt) {
14:     let line = readlineSync.question(prompt);
15:     if (line === '') {
16:         throw new Error('Missing integer');
17:
18:     let n = Number(line);
19:     if (!Number.isInteger(n))
20:         throw new Error('Not an integer');
21:
22:     return n;
23: }
24:
25: //-----
26:
27: function main() {
28:     try {
29:         let n1 = readInt('Numerator 1: ');
30:         let d1 = readInt('Denominator 1: ');
31:         let n2 = readInt('Numerator 2: ');
32:         let d2 = readInt('Denominator 2: ');
33:
34:         let f1 = new fraction.Fraction(n1, d1);
35:         let f2 = new fraction.Fraction(n2, d2);
36:
37:         process.stdout.write('f1: ' + f1.toString() + '\n');
38:         process.stdout.write('f2: ' + String(f2) + '\n');
39:
40:         if (f1 === f2)
41:             process.stdout.write('f1 is identical to f2\n');
42:         else
43:             process.stdout.write('f1 is not identical to f2\n');
44:
45:         let compare = f1.compareTo(f2);
46:         if (compare < 0)
47:             process.stdout.write('f1 is less than f2\n');
48:         if (compare > 0)
49:             process.stdout.write('f1 is greater than f2\n');
50:         if (compare === 0)
51:             process.stdout.write('f1 is equal to f2\n');
52:
53:         let f3;
54:
55:         f3 = f1.negate();
56:         process.stdout.write('-f1: ' + String(f3) + '\n');
57:
58:         f3 = f1.add(f2);
59:         process.stdout.write('f1 + f2: ' + String(f3) + '\n');
60:
61:         f3 = f1.subtract(f2);
62:         process.stdout.write('f1 - f2: ' + String(f3) + '\n');
63:
64:         f3 = f1.multiply(f2);
65:         process.stdout.write('f1 * f2: ' + String(f3) + '\n');

```

fraction3client.js (Page 2 of 2)

```

66:
67:         f3 = f1.divide(f2);
68:         process.stdout.write('f1 / f2: ' + String(f3) + '\n');
69:     }
70:     catch (e) {
71:         process.stderr.write(e + '\n');
72:     }
73: }
74:
75: if (require.main === module)
76:     main();

```

fraction4.js (Page 1 of 2)

```

1: //-----
2: // fraction4.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const euclid = require('./euclid.js');
9:
10: function Fraction(num=0, den=1) {
11:     if (arguments.length > 2)
12:         throw new Error('Too many arguments');
13:
14:     if (den === 0)
15:         throw new Error('Denominator cannot be zero');
16:
17:     this._num = num;
18:     this._den = den;
19:
20:     if (this._den < 0) {
21:         this._num *= -1;
22:         this._den *= -1;
23:     }
24:     if (this._num === 0)
25:         this._den = 1;
26:     else {
27:         let gcden = euclid.gcd(this._num, this._den);
28:         this._num /= gcden;
29:         this._den /= gcden;
30:     }
31: }
32:
33: Fraction.prototype.toString = function() {
34:     return String(this._num) + '/' + String(this._den);
35: };
36:
37: Fraction.prototype.compareTo = function(other) {
38:     if ((this._num * other._den) < (other._num * this._den)) return -1;
39:     if ((this._num * other._den) > (other._num * this._den)) return 1;
40:     return 0;
41: };
42:
43: Fraction.prototype.negate = function() {
44:     return new Fraction(-this._num, this._den);
45: };
46:
47: Fraction.prototype.add = function(other) {
48:     let newNum = (this._num * other._den) + (other._num * this._den);
49:     let newDen = this._den * other._den;
50:     return new Fraction(newNum, newDen);
51: };
52:
53: Fraction.prototype.subtract = function(other) {
54:     let newNum = (this._num * other._den) - (other._num * this._den);
55:     let newDen = this._den * other._den;
56:     return new Fraction(newNum, newDen);
57: };
58:
59: Fraction.prototype.multiply = function(other) {
60:     let newNum = this._num * other._num;
61:     let newDen = this._den * other._den;
62:     return new Fraction(newNum, newDen);
63: };
64:
65: Fraction.prototype.divide = function(other) {

```

fraction4.js (Page 2 of 2)

```

66:     let newNum = this._num * other._den;
67:     let newDen = this._den * other._num;
68:     return new Fraction(newNum, newDen);
69: };
70:
71: module.exports = { Fraction };

```

fraction4client.js (Page 1 of 2)

```

1: //-----
2: // fraction4client.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const readline = require('readline-sync');
9: const fraction = require('./fraction4.js');
10:
11: //-----
12:
13: function readInt(prompt) {
14:     let line = readline.question(prompt);
15:     if (line === '') {
16:         throw new Error('Missing integer');
17:
18:     let n = Number(line);
19:     if (!Number.isInteger(n))
20:         throw new Error('Not an integer');
21:
22:     return n;
23: }
24:
25: //-----
26:
27: function main() {
28:     try {
29:         let n1 = readInt('Numerator 1: ');
30:         let d1 = readInt('Denominator 1: ');
31:         let n2 = readInt('Numerator 2: ');
32:         let d2 = readInt('Denominator 2: ');
33:
34:         let f1 = new fraction.Fraction(n1, d1);
35:         let f2 = new fraction.Fraction(n2, d2);
36:
37:         process.stdout.write('f1: ' + f1.toString() + '\n');
38:         process.stdout.write('f2: ' + String(f2) + '\n');
39:         process.stdout.write('f2: ' + f2 + '\n');
40:
41:         if (f1 === f2)
42:             process.stdout.write('f1 is identical to f2\n');
43:         else
44:             process.stdout.write('f1 is not identical to f2\n');
45:
46:         let compare = f1.compareTo(f2);
47:         if (compare < 0)
48:             process.stdout.write('f1 is less than f2\n');
49:         if (compare > 0)
50:             process.stdout.write('f1 is greater than f2\n');
51:         if (compare === 0)
52:             process.stdout.write('f1 is equal to f2\n');
53:
54:         let f3;
55:
56:         f3 = f1.negate();
57:         process.stdout.write('-f1: ' + String(f3) + '\n');
58:
59:         f3 = f1.add(f2);
60:         process.stdout.write('f1 + f2: ' + String(f3) + '\n');
61:
62:         f3 = f1.subtract(f2);
63:         process.stdout.write('f1 - f2: ' + String(f3) + '\n');
64:
65:         f3 = f1.multiply(f2);

```

fraction4client.js (Page 2 of 2)

```

66:         process.stdout.write('f1 * f2: ' + String(f3) + '\n');
67:
68:         f3 = f1.divide(f2);
69:         process.stdout.write('f1 / f2: ' + String(f3) + '\n');
70:     }
71:     catch (e) {
72:         process.stderr.write(e + '\n');
73:     }
74: }
75:
76: if (require.main === module)
77:     main();

```

fraction5.js (Page 1 of 2)

```

1: //-----
2: // fraction5.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const euclid = require('./euclid.js');
9:
10: class Fraction {
11:     constructor(num=0, den=1) {
12:         if (arguments.length > 2)
13:             throw new Error('Too many arguments');
14:
15:         if (den === 0)
16:             throw new Error('Denominator cannot be zero');
17:
18:         this._num = num;
19:         this._den = den;
20:
21:         if (this._den < 0) {
22:             this._num *= -1;
23:             this._den *= -1;
24:         }
25:         if (this._num === 0)
26:             this._den = 1;
27:         else {
28:             let gcden = euclid.gcd(this._num, this._den);
29:             this._num /= gcden;
30:             this._den /= gcden;
31:         }
32:     }
33:
34:     toString() {
35:         return String(this._num) + '/' + String(this._den);
36:     }
37:
38:     compareTo(other) {
39:         if ((this._num * other._den) < (other._num * this._den))
40:             return -1;
41:         if ((this._num * other._den) > (other._num * this._den))
42:             return 1;
43:         return 0;
44:     }
45:
46:     negate() {
47:         return new Fraction(-this._num, this._den);
48:     }
49:
50:     add(other) {
51:         let newNum = (this._num * other._den) + (other._num * this._den);
52:         let newDen = this._den * other._den;
53:         return new Fraction(newNum, newDen);
54:     }
55:
56:     subtract(other) {
57:         let newNum = (this._num * other._den) - (other._num * this._den);
58:         let newDen = this._den * other._den;
59:         return new Fraction(newNum, newDen);
60:     }
61:
62:     multiply(other) {
63:         let newNum = this._num * other._num;
64:         let newDen = this._den * other._den;
65:         return new Fraction(newNum, newDen);

```

fraction5.js (Page 2 of 2)

```

66:     }
67:
68:     divide(other) {
69:         let newNum = this._num * other._den;
70:         let newDen = this._den * other._num;
71:         return new Fraction(newNum, newDen);
72:     }
73: }
74:
75: module.exports = { Fraction };

```

fraction5client.js (Page 1 of 2)

```

1: //-----
2: // fraction5client.js
3: // Author: Bob Dondero
4: //-----
5:
6: 'use strict';
7:
8: const readlineSync = require('readline-sync');
9: const fraction = require('./fraction5.js');
10:
11: //-----
12:
13: function readInt(prompt) {
14:     let line = readlineSync.question(prompt);
15:     if (line === '') {
16:         throw new Error('Missing integer');
17:
18:     let n = Number(line);
19:     if (!Number.isInteger(n))
20:         throw new Error('Not an integer');
21:
22:     return n;
23: }
24:
25: //-----
26:
27: function main() {
28:     try {
29:         let n1 = readInt('Numerator 1: ');
30:         let d1 = readInt('Denominator 1: ');
31:         let n2 = readInt('Numerator 2: ');
32:         let d2 = readInt('Denominator 2: ');
33:
34:         let f1 = new fraction.Fraction(n1, d1);
35:         let f2 = new fraction.Fraction(n2, d2);
36:
37:         process.stdout.write('f1: ' + f1.toString() + '\n');
38:         process.stdout.write('f2: ' + String(f2) + '\n');
39:
40:         if (f1 === f2)
41:             process.stdout.write('f1 is identical to f2\n');
42:         else
43:             process.stdout.write('f1 is not identical to f2\n');
44:
45:         let compare = f1.compareTo(f2);
46:         if (compare < 0)
47:             process.stdout.write('f1 is less than f2\n');
48:         if (compare > 0)
49:             process.stdout.write('f1 is greater than f2\n');
50:         if (compare === 0)
51:             process.stdout.write('f1 is equal to f2\n');
52:
53:         let f3;
54:
55:         f3 = f1.negate();
56:         process.stdout.write('-f1: ' + String(f3) + '\n');
57:
58:         f3 = f1.add(f2);
59:         process.stdout.write('f1 + f2: ' + String(f3) + '\n');
60:
61:         f3 = f1.subtract(f2);
62:         process.stdout.write('f1 - f2: ' + String(f3) + '\n');
63:
64:         f3 = f1.multiply(f2);
65:         process.stdout.write('f1 * f2: ' + String(f3) + '\n');

```

fraction5client.js (Page 2 of 2)

```

66:
67:         f3 = f1.divide(f2);
68:         process.stdout.write('f1 / f2: ' + String(f3) + '\n');
69:     }
70:     catch (e) {
71:         process.stderr.write(e + '\n');
72:     }
73: }
74:
75: if (require.main === module)
76:     main();

```