

Princeton University

COS 217: Introduction to Programming Systems

The Valgrind Tool

What is it?

Valgrind is a tool to help you analyze your application's dynamic memory management. It can help you find memory leaks, multiple frees, and dereferences of dangling pointers. It may help you find other dynamic memory management errors as well. Valgrind is an open-source tool that has been developed by multiple programmers over multiple years. Browse to <http://valgrind.org/> for details.

How do I use it?

Suppose you wish to use Valgrind to help you debug a program named `mypgm`. Further suppose that `mypgm` consists of source code files `mysourcecode1.c` and `mysourcecode2.c`. Assuming that you've configured your armlab programming environment as described in the first precept, follow these steps:

(1) Issue a `gcc217` command with the `-g` option to preprocess, compile, and assemble `mysourcecode1.c` and `mysourcecode2.c`:

```
gcc217 -g -c sourcecode1.c
gcc217 -g -c sourcecode2.c
```

(2) Issue a `gcc217` command with the `-g` option command to link `mysourcecode1.o` and `mysourcecode2.o`, thus creating executable file `mypgm`:

```
gcc217 -g sourcecode1.o sourcecode2.o -o mypgm
```

Note that steps 1 and 2 can be combined by issuing a single command:

```
gcc217 -g sourcecode1.c sourcecode2.c -o mypgm
```

(3) Execute `mypgm` through the `valgrind` program, by issuing a command consisting of `valgrind` followed by your program's name (and command-line arguments, as appropriate):

```
valgrind ./mypgm arg1 arg2 ...
```

Valgrind writes messages to `stderr`. It does so as your program executes, so Valgrind's messages often are interspersed with your program's output. If Valgrind writes many

messages, then you might find it convenient to redirect `stderr` to a file, and then examine the file subsequently:

```
valgrind ./mypgm arg1 arg2 ... 2> valgrindreport
cat valgringreport
```

Valgrind is a powerful tool; its intended audience is experienced C programmers. So newcomers to C might consider its output to be cryptic.

Generally, you should read Valgrind's output from bottom to top. Doing so provides a function-call trace from your `main()` function, perhaps through multiple levels of function calls, to the function that was executing at the time Valgrind detected a problem. That information often is helpful, even if the error is elsewhere in your code.

Feel free to contact your preceptor if you have trouble interpreting the output of Valgrind.

Copyright © 2019 by Robert M. Dondoro, Jr.